



## SAFETY DATA SHEET

EURO SILICONE SPRAY

Page: 1

Compilation date: 17/04/2013

Revision No: 2

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name:** EURO SILICONE SPRAY

**Product code:** SND450

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** Press consumable for the printing industry

#### 1.3. Details of the supplier of the safety data sheet

**Company name:** Uk Euroconnect Ltd

Shoats Barn

Shelvin Farm

Canterbury

Kent

CT4 6RL

United Kingdom

**Tel:** +44 (0) 1303 844 000

**Fax:** +44 (0) 1303 844 001

**Email:** sales@ukeuro.com

#### 1.4. Emergency telephone number

**Emergency tel:** +44 (0) 1303 844 000

### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**Classification under CHIP:** F+: R12; Xi: R38; N: R51/53; -: R67

**Classification under CLP:** Aquatic Chronic 2: H411; Flam. Aerosol 1: H222; Skin Irrit. 2: H315; STOT SE 3: H336

**Most important adverse effects:** Extremely flammable. Irritating to skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.

#### 2.2. Label elements

##### Label elements under CLP:

**Hazard statements:** H222: Extremely flammable aerosol.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

**Signal words:** Danger

**Hazard pictograms:** GHS02: Flame

[cont...]

# SAFETY DATA SHEET

## EURO SILICONE SPRAY

Page: 2

GHS07: Exclamation mark

GHS09: Environmental



**Precautionary statements:** P211: Do not spray on an open flame or other ignition source.  
P251: Pressurized container: Do not pierce or burn, even after use.  
P271: Use only outdoors or in a well-ventilated area.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P312: Call a POISON CENTER or doctor if you feel unwell.

### Label elements under CHIP:

**Hazard symbols:** Extremely flammable.

Irritant.

Dangerous for the environment.



**Risk phrases:** R12: Extremely flammable.  
R38: Irritating to skin.  
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R67: Vapours may cause drowsiness and dizziness.

**Safety phrases:** S38: In case of insufficient ventilation, wear suitable respiratory equipment.  
S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

**Precautionary phrases:** Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.  
Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

### 2.3. Other hazards

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

**PBT:** This product is not identified as a PBT substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

[cont...]

# SAFETY DATA SHEET

EURO SILICONE SPRAY

Page: 3

## Hazardous ingredients:

### BUTANE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
203-448-7	106-97-8	F+: R12 Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	30-50%

### HEPTANE

205-563-8	142-82-5	F: R11; Xn: R65; Xi: R38; -: R67; N: R50/53	Flam. Liq. 2: H225; Asp. Tox. 1: H304; Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Acute 1: H400; Aquatic Chronic 1: H410	10-30%
-----------	----------	---	---	--------

### ISOBUTANE

200-857-2	75-28-5	F+: R12 Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10-30%
-----------	---------	---	-------------------------------------	--------

### CYCLOPENTANE

206-016-6	287-92-3	F: R11; -: R52/53	Flam. Liq. 2: H225; Aquatic Chronic 3: H412	1-10%
-----------	----------	-------------------	---	-------

### PENTANE

203-692-4	109-66-0	F+: R12; N: R51/53; Xn: R65; -: R66; -: R67	Flam. Liq. 2: H225; Asp. Tox. 1: H304; STOT SE 3: H336; Aquatic Chronic 2: H411; -: EUH066	<1%
-----------	----------	---	--	-----

### N-HEXANE

203-777-6	110-54-3	F: R11; Xi: R38; Xn: R48/20; Xn: R62; Xn: R65; -: R67; N: R51/53	Flam. Liq. 2: H225; Repr. 2: H361f; Asp. Tox. 1: H304; STOT RE 2: H373; Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 2: H411	<1%
-----------	----------	--	---	-----

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

[cont...]

# SAFETY DATA SHEET

EURO SILICONE SPRAY

Page: 4

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Eye bathing equipment should be available on the premises.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Do not use water jet as this may spread the fire

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

**Reference to other sections:** See section 7 for information on safe handling. See Section 8 for information on personal protective equipment. See section 13 for disposal information.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

[cont...]

# SAFETY DATA SHEET

EURO SILICONE SPRAY

Page: 5

## 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

**Suitable packaging:** It is recommended to store in original packaging

## 7.3. Specific end use(s)

**Specific end use(s):** Pressroom sundry item

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

**BUTANE**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1450 mg/m <sup>3</sup>	1810 mg/m <sup>3</sup>	-	-

**HEPTANE**

UK	2100 mg/m <sup>3</sup>	8400 mg/m <sup>3</sup>	-	-
----	------------------------	------------------------	---	---

**ISOBUTANE**

UK	2400 mg/m <sup>3</sup>	9600 mg/m <sup>3</sup>	-	-
----	------------------------	------------------------	---	---

**PENTANE**

UK	1800 mg/m <sup>3</sup>	-	-	-
----	------------------------	---	---	---

**N-HEXANE**

UK	72 mg/m <sup>3</sup>	-	-	-
----	----------------------	---	---	---

### 8.1. DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Nitrile gloves. Viton gloves. PVA gloves. Gloves should be replaced regularly or if any change in appearance is noticed. Ensure gloves are manufactured/tested in accordance with BS EN 374. Penetration times carried out according to EN 374 part III are not always practical, therefore max. wearing time of 50% of penetration time is recommended.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**Environmental:** An environmental assessment must be made to ensure compliance with local environmental legislation.

[cont...]

# SAFETY DATA SHEET

EURO SILICONE SPRAY

Page: 6

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

State: Aerosol

Flash point°C: <-40C

### 9.2. Other information

Other information: No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

Conditions to avoid: Heat. Sources of ignition. Flames.

### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

Hazardous ingredients:

#### HEPTANE

IVN	MUS	LD50	222	mg/kg
-----	-----	------	-----	-------

#### CYCLOPENTANE

ORL	MUS	LD50	12800	mg/kg
ORL	RAT	LD50	11400	mg/kg

[cont...]

# SAFETY DATA SHEET

EURO SILICONE SPRAY

Page: 7

## PENTANE

IVN	MUS	LD50	446	mg/kg
ORL	RAT	LD50	400	mg/kg

## N-HEXANE

IPR	RAT	LDLO	9100	mg/kg
IVN	MUS	LDLO	831	mg/kg
ORL	RAT	LD50	25	gm/kg

### Relevant effects for mixture:

Effect	Route	Basis
Irritation	DRM	Hazardous: calculated

## Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity values:** No data available.

### 12.2. Persistence and degradability

**Persistence and degradability:** No data available.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No data available.

### 12.4. Mobility in soil

**Mobility:** No data available.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT substance.

### 12.6. Other adverse effects

**Other adverse effects:** Toxic to aquatic organisms. Toxic to soil organisms.

## Section 13: Disposal considerations

[cont...]

# SAFETY DATA SHEET

EURO SILICONE SPRAY

Page: 8

## 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Disposal of packaging:** Arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN1950

### 14.2. UN proper shipping name

**Shipping name:** AEROSOLS

### 14.3. Transport hazard class(es)

**Transport class:** 2

### 14.4. Packing group

### 14.5. Environmental hazards

**Environmentally hazardous:** Yes

**Marine pollutant:** Yes

### 14.6. Special precautions for user

**Special precautions:** No special precautions.

**Tunnel code:** D/E

**Transport category:** 3

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** EU Legislation Regulation (EC) No 1907/2006 REACH. Regulation (EC) No 1272/2008 CLP.

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

**Phrases used in s.2 and 3:** EUH066: Repeated exposure may cause skin dryness or cracking.

H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

[cont...]



## SAFETY DATA SHEET

### EURO SILICONE SPRAY

Page: 9

H225: Highly flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H361f: Suspected of damaging fertility.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

R11: Highly flammable.

R12: Extremely flammable.

R38: Irritating to skin.

R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R62: Possible risk of impaired fertility.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.